



E&E LIGHTING
AUSTRALIA

PRODUCT CODE: EXSLIDE-ST

ALL-IN-ONE SLIDE CONNECT LED EXIT

PRODUCT INFORMATION

PRODUCT CODE	DESCRIPTION
EXSLIDE-ST	All-in-One Slide Connect Surface Mount LED Self Test Exit

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	2kg (unit) - 10kg (box)
Dimension (L x W x H)	370mm x 70mm x 230mm



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Operating Voltage	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Switchable Self Test
Construction	Polycarbonate Body and Diffuser
Classification	C0 D6.3 C90 D6.3
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m
D6.3	8.5	8.8	8.9	9.1

NOTE: This product serves a dual function as both a 24-meter Exit Sign and an Emergency Luminaire, compliant with the following emergency classifications.
Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2018

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BSLIDE	LiFePO4 Lithium Battery, 3.2V 1500mAh

The product details outlined in this document are accurate as of the document's version date. We reserve the right to modify product design, specifications, or materials without prior notice due to ongoing product improvement policy and changes to industry standards. We recommend confirming the applicable specifications at the time of placing your order to ensure alignment with the most current information

Version: 0325-02



0487 248 481



www.eelighting.com.au



sales@eelighting.com.au