



E&E LIGHTING  
AUSTRALIA

# PRODUCT CODE: SBUNKERWP

## LED WEATHERPROOF BUNKER

### PRODUCT INFORMATION

| PRODUCT CODE | DESCRIPTION                                          |
|--------------|------------------------------------------------------|
| SBUNKERWP    | 20W LED Weatherproof Bunker                          |
| SBUNKERWPDS  | 20W LED Weatherproof Bunker<br>with Microwave Sensor |

### ORDERING INFORMATION

|                       |                           |
|-----------------------|---------------------------|
| Carton Qty            | 5 pieces                  |
| Weight                | 2.9kg (unit) - 15kg (box) |
| Dimension (L x W x H) | 315mm x 315mm x 85mm      |



### OPERATIONAL INFORMATION

#### TECHNICAL SPECIFICATIONS

|                       |                                                        |
|-----------------------|--------------------------------------------------------|
| Operating Voltage     | 220-260V; 50Hz                                         |
| Operating Temperature | -25° - 45° C                                           |
| IP Rating             | IP65                                                   |
| IK Rating             | IK10                                                   |
| Wiring                | Large Terminal Block                                   |
| Mounting Type         | Surface Mount                                          |
| Construction          | Die-cast Aluminium Body with<br>Polycarbonate Diffuser |
| Standards             | AS/NZS 60598.1<br>EMC                                  |

#### BATTERY AND LEDS

|                    |                                |
|--------------------|--------------------------------|
| Power Consumption  | 20W                            |
| Power Factor       | >0.95                          |
| Lens               | LED Lamp Rated at 50,000 Hours |
| Lumens Output      | 2200lm                         |
| Colour Temperature | 4000k                          |
| Beam Angle         | 140 Degrees                    |
| CRI                | <80                            |

The product details outlined in this document are accurate as of the document's version date. We reserve the right to modify product design, specifications, or materials without prior notice due to ongoing product improvement policy and changes to industry standards. We recommend confirming the applicable specifications at the time of placing your order to ensure alignment with the most current information.

Version: 0325-02



0487 248 481



[www.eelighting.com.au](http://www.eelighting.com.au)



[sales@eelighting.com.au](mailto:sales@eelighting.com.au)